Safety Data Sheet

			So	ection 1 - Pr	oduct Infor	mation				
Draduct Nama	· hurricano						Cumplion	Intercon Chemical Company		
Product Name: hurricane				ne: 1-314-771-6600		Supplier:	Intercon Chemical Company			
					Addr			1100 Central Industrial Drive		
roduct use:	High Butyl Foa	ming Degreaser		ntact: CHEMTRE				St. Louis, MO 63110		
			56	ection 2 - Ha	izard identi	tication				
HS Classificat	tion: Skin Corros	ion/Irritation - (cate	<u> </u>							
				Section 2.1	- Label Eler					
	Hazar	d Pictograms				Precau	tionary Stateme	ents:		
		PS						fter handling. Do not breathe mist or dus		
	<u> </u>	<u>₩</u> 🐔		IF ON SKIN(or hair): Remove immediately all contaminated clothing. Rinse skin with water. Wash						
				contaminated clothing before reuse. IF IN EYES: Rinse cautiously with water for several minutes. Remove contacts if present and easy to do.						
				Continue rinsin				,		
	Hazaro	d Statements:				Do NOT induce	-			
Causes severe skin burns and eye damage.						· ·		fortable for breathing.		
				-	Immediately call a POISON CENTER or physician. Specific treatment(see section 4 of the sds).					
					•	•	s to an approve	d waste handling facility.		
				Section 3	- Composit	ion				
	Cher	mical Name		Jection 3	•	AS #		Percent w/w		
-butoxy ethai		inical Name			111-76-2			5		
odium Xylene					1300-72-7			2.8		
	•							-		
Sodium Hydro	xide				1310)-73-2		2.5		
			9	Section 4 - F	irst Aid Me	asures				
F ON SKIN(or	hair): Remove in	nmediately all conta					hing hefore reus	se.		
	-	th water for several								
E SWALLOWE	D: Binco mouth	Do NOT induce von	niting	<u> </u>	<u> </u>					
	· · · · · · · · · · · · · · · · · · ·									
		air and keep at rest p NTER or physician.	osition comforta	ble for breatning						
illilediately C	ali a POISON CLI	VIEW OF PHYSICIAN.	•	:						
	1		Section	n 5 - Fire and	Explosion	T				
lash Point:		Limits		ctinguishing Med				es: Avoid exposure to fumes or vapors. ressurized breathing apparatus		
None	١	LEL: NA		Water spray or fog, foam, dry chemical, carbon dioxide, alcohol foam, if product			MSHA/NIOSH Approved or equivalent to maintain TLV. UNUSUAL FIRE			
None	(UEL: NA	involved	EXPLOSION HAZARD: Pro			ZARD: Product	will not burn.		
	•		_ '	n 6 - Accide	ntal Releas	e Measures				
				ection 7 - Ha						
Store locked u	up. Store unrigh	t in original closed o					ing. Remove and	I wash contaminated clothing before reu		
	,	_ Ja. 3,000 0	2		5		5 3			
			Sec	ction 8 - Exp	osure Cont	rols/PPE				
Ingredient OSHA PEL:		ACGIH TLV	<u> </u>			Ge	eneral Hygiene Considerations:			
2-butoxy ethanol		50ppm	50ppm	Respiratory: Not normally re		equired Handle in accor		e in accordance with good industrial hygiene and		
						safety practice		practices. Provide suitable facilities for quick		
		not listed		splash proof go			ushing of the eyes and body in case of			
odium Hydro	xide	2mg/m ³	2mg/m ³	Skin: alkali resistant		contact or splash hazard.		sn nazard.		
		I	1	Ventilation	Normal room v	entilation	I			

Section 9 - Physical and Chemical Properties									
Appearance	odor	odor threshold	рН	Melting Point	Boiling point	rate	Flammability	flammability limits	pressure
Fluorescent Green Liquid	Pine like	NE	13	NE	212ºF	>1.0 (water =1)	No	NA	17mm(Hg)
Orecon Enquira	· ····c ····c	INE	13	IVL	212-1	(water 1)	110	INA	1711111(116)
Vapor Density	Density	Specific Gravity	pH(use dil)	Solubility(H₂O)	Partition coefficient	Auto Ignition temp	Viscosity	Decomposition Temp	
.62(air = 1)	8.58lbs/gal	1.03	10	complete	NE	NA	Thin	NE	
Section 10 Stability and Beactivity									

Section 10 - Stability and Reactivity

Product is stable. Hazardous polymerization will not occur. It is incompatible with strong oxidizing agents. If burned normal combustion products such as Carbon Dioxide, Carbon Monoxide and Nitrous Oxides may occur.

Section 11- Toxicological Information Acute **STOST** Acute toxicity(oral toxicity(derm. Reproduct. Repeated LD50) rat LD50)rabbit Toxicity exposure ingredient Skin and Eye Carcinogen Mutagen STOST -single Exposure 2-butoxy ethanol 470mg/kg 220mg/kg irritant no evidence no evidence no evidence No data available No data Sodium Xylene Sulphonate 7200mg/kg 2000mg/kg irritant no evidence no evidence not listed No data available No data Sodium Hydroxide 200mg/kg 1350mg/kg corrosive no evidence no evidence not listed No data available No data

Other:

Section 13 - Disposal Considerations

No information available

Products covered by this sds, in their original form, are considered to be hazardous waste, waste code D002, according to RCRA(40 CFR 261). Care should be used to avoid introduction to sewers and waterways. Dispose of in accordance with applicable Federal, State and Local regulations.

Section 14 - Transport Information

UN number	Basic Description(DOT)	Class	Packing Group	LTD QTY
UN1719	Caustic Alkali Liquids, n.o.s. (contains Sodium Hydroxide)	8	П	< 1L

Section 15 - Regulatory Information

SARA Title III(EPCRA): Glycol Ethers

CERCLA: Glycol Ethers, Sodium Hydroxide. For more information consult 40 CFR parts 302, 355, 370, 372, and 40 CFR part 68

Section 16 - Other Information

	HMIS:	Health - 3	Flam 0	R - 0	PPE
			•		

Date Prepared: 14-Nov-2019 Prepared by: Environmental, Health and Safety Administrator.

The information provided in this Safety Data Sheet is correct to the best of our knowledge and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal, and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with materials or in any process, unless specified in the text.

Legend for Abbreviations: NA - not applicable NE - Not Established