

# hurricane

HEAVY DUTY ALKALINE SOLVENT DEGREASER

# **Product Properties**

COLOR: Clear, Fluorescent Green ODOR: Characteristic Odor

VISCOSITY: 10 cps

pH: 13
FLASH POINT: None
FOAMING: Moderate
DETERGENCY: Excellent

SOLUBILITY IN WATER: Complete

RINSABILITY: Complete

## **Description**

This product is a high strength alkaline solvent degreaser. It incorporates advanced concepts in chemical soil removal to remove a wide range of soils. Safe for use on detergent resistant surfaces, this degreaser makes fast work of even the toughest cleaning tasks. Can be used manually, with spraying equipment or through foam generating equipment.

#### Features...Benefits

### **Directions**

GENERAL CLEANING: Dilute at 1:10 to 1:50 with water depending on soil conditions. Spray, brush or mop on. Rinse or wipe off. Always rinse food contact surfaces with potable water after cleaning.

HEAVY DUTY AND INDUSTRIAL CLEANING: Dilute at 1:2 to 1:10. Spray, brush or mop on. Allow time to penetrate soils. Agitate if necessary. Rinse. KITCHENS: Use solution 1 part cleaner to 6 parts water to clean vent hoods, fans, blowers, appliances, burners, etc. Use dilution of 1 to 10 in deep-fat fryer, heat to just below boiling, empty and drain. Food contact surfaces should always be rinsed with potable water before reuse.

SPRAY CLEANING: Dilute at 2 to 4 oz. per gallon of water. Spray and wipe surfaces. Repeat if necessary.

INDUSTRIAL DEGREASING: Dilute with 2 to 4 parts hot water; spray on, soak 5 to 10 minutes, rinse. High pressure spray gives spectacular cleaning results.

## **Safety Information**

KEEP OUT OF REACH OF CHILDREN

DANGER: CONTAINS ALKALINE BUILDERS. May cause burns to eyes and skin. Harmful if swallowed. Avoid contact with eyes, skin and clothing. In case of contact with eyes, flush with plenty of water and seek medical attention. In case of contact with skin, flush with plenty of water. Seek medical attention if irritation persists. If swallowed, give plenty of water or milk and seek medical attention.

1100 Central Industrial Dr. St. Louis, Missouri, 63110

> toll free: 800 325 9218 main: 314 771 6600 fax: 314 771 6608

www.interconchemical.com



Letter of guarantee available upon request.

180223-694F © INTERCON 2018 REFER TO PRODUCT LABEL AND SDS FOR ADDITIONAL INFORMATION